

RICOH FT4615/FT4618



The Straightforward and Compact Copier

Focus on Compactness and Reliability

The Ricoh FT4615/FT4618 is one of the most compact A3 copiers on the market. It has the power you need to produce black-and-white copies simply and reliably. The FT4615/FT4618 packs all Ricoh's experience and reliability into its compact size, and does it in an environmentally conscious way. It features a fast warm-up time, producing the first copy after only 6.9/6.5 seconds, and a speed of 15/18 copies per minute. Add this to the high-quality A3 copying, auto-start mode and large paper capacity, and you have the ideal office partner.



Simply copying you can rely on



Easy operation

The new FT4615/FT4618's user-friendly approach is apparent from one glance at the simplified control panel. Large keys and ten user codes ensure easy access to a host of powerful features for flexible, trouble-free copying. The powerful zoom feature can enlarge or reduce your documents from 50 to 200%. Preset magnification ratios are available for most standard paper sizes.

Flexible and large paper capacity

The FT4615/FT4618 is your ideal partner for flexible and efficient document handling. The FT4615 is equipped with one 500-sheet tray and the FT4618 with two 250-sheet paper trays. On top of that they also have an independent 80-sheet bypass, offering you the choice of different paper sizes.

Dependability and excellent image quality

Built to last, the FT4615/FT4618 features a short paper path for reduced wear and tear and greater reliability. This is combined with high-grade Ricoh technology such as fine toner particles and a sensitive OPC drum for outstanding image quality. The result is sharp, clear images with crisp fine lines and dense black solids.

Thanks to features like Photo Mode and Series Copy Mode the same high quality standards of reproduction are guaranteed from virtually any kind of original, including photographs.

Environmentally conscious

Protecting the environment is an important part of the Ricoh philosophy.

The FT4615/FT4618's energy saver feature reduces power consumption when the machine is not in use, while reducing ozone and heat emissions to a minimum. Simply switch on the machine again by touching a button on the display. Finally, the belt drive system dampens mechanical noise and makes the FT4615/FT4618 a quiet and unobtrusive asset.

Thanks to Ricoh's continued attention to environmental standards, the FT4615/FT4618 boasts an ecological design that facilitates dismantling and recycling of parts. The toner recycling feature collects leftover toner from the drum and returns it to the toner supply unit for reuse. This results in no wastage and longer-lasting toner supply. Material symbol marking of plastic parts makes dismantling and recycling a straightforward process.

Performance under pressure

The Ricoh FT4615/FT4618 packs a host of options designed to raise the productivity of your organisation and to save critical time when handling large copying jobs. The ADF holds up to 30 originals and feeds your documents automatically, keeping up with the fast 15/18 cpm output. With the optional 10-bin sorter, the FT4615/FT4618 can sort your copies electronically in convenient sets of up to 20 sheets per bin.

Other features

- Automatic exposure
- 10 user codes

RICOH FT4615/FT4618



FT4615 with options



FT4618 with options

FT4615 Specifications

Configuration:	Desktop
Copying Process:	Dry electrostatic transfer system
Maximum Original Size:	A3
Copy Size:	Max. A3 (297 x 420 mm) Min. A6 (105 x 148 mm)
Multiple Copying:	1 ~ 99
Warm-up Time:	Max. 35 sec.
First Copy Speed:	Max. 6.9 sec. (A4/LT)
Copy Speed:	A4/LT: 15 cpm A4R/LT Length: 12 cpm B4/Legal: 10 cpm A3/DLT: 9 cpm
Preset Reproduction Ratios:	4R: 50, 71, 82, 93% 3E: 122, 141, 200%
Zoom Up and Down:	50 ~ 200%
Paper Capacity:	One 500-sheet tray plus 80-sheet bypass tray
Copy Paper Weight:	64 ~ 90g/m ² 52 ~ 157g/m ²
Power Source:	220-230V/50-60 Hz
Power Consumption:	Max. 1.1 kW (Mainframe only)
Dimensions (W x D x H):	579 x 560 x 420 mm
Weight:	40.5 kg

FT4618 Specifications

Configuration:	Desktop
Copying Process:	Dry electrostatic transfer system
Maximum Original Size:	A3
Copy Size:	Max. A3 (297 x 420 mm) Min. A6 (105 x 148 mm)
Multiple Copying:	1 ~ 99
Warm-up Time:	Max. 45 sec.
First Copy Speed:	Max. 6.5 sec. (A4/LT)
Copy Speed:	A4/LT: 18 cpm A4R/LT Length: 13 cpm B4/Legal: 11 cpm A3/DLT: 10 cpm
Preset Reproduction Ratios:	4R: 50, 71, 82, 93% 3E: 122, 141, 200%
Zoom Up and Down:	50 ~ 200%
Paper Capacity:	Two 250-sheet trays plus 80-sheets bypass tray
Copy Paper Weight:	64 ~ 90g/m ² 52 ~ 157g/m ²
Power Source:	220-230V/50-60 Hz
Power Consumption:	Max. 1.1 kW (Mainframe only)
Dimensions (W x D x H):	579 x 560 x 465 mm
Weight:	43.5 kg

Auto Document Feeder DF44 (Optional)

Original Size:	A3 to A5
Original Weight:	52 to 105g/m ²
Original Stack Capacity:	30 sheets (80g/m ²)
Original Feeding Speed:	FT4615: 15 sheets/min. (A4) FT4618: 18 sheets/min. (A4)

Power Consumption:	45 W
Dimensions (W x D x H):	590 x 443 x 87.5 mm
Weight:	7.0 kg

Sorter CS150 (Optional)

Number of Bins:	10
Paper Size:	Max. A3 (297 x 420 mm) Min. A5 (148 x 210 mm)
Bin Capacity:	20 sheets/bin (A4)
Power Consumption:	15 W
Dimensions (W x D x H):	402 x 447 x 217 mm
Weight:	7.5 kg

Specifications are subject to change without notice.
The colour(s) of the actual product may vary from the colour(s) shown in this brochure.



Ricoh has determined that this product meets the ENERGY STAR guidelines for energy efficiency.



RICOH
Image Communication

Home Page: <http://www.ricoh-europe.com>

Ricoh believes in conserving the earth's precious natural resources.
This brochure is printed on environmentally friendly paper.

RICOH EUROPE B.V. Groenelaan 3, P.O. Box 114, 1180 AC Amstelveen, The Netherlands. Phone: +31 (0)20-5474111 Fax: +31 (0)20-6418601

For more information, please contact: