

### **BASIC COMPOSITION**

Copying Process Copying Type

**Original Reading Method** 

Type

Original Table

Resolution **Print Speed** Warm-Up Time

First Copy Time **Duty Cycle** Multiple Copying Acceptable Paper Size

Acceptable Paper Type

Memory Reduction/Enlargement

Bypass Control Panel Paper Supply

Toner Control Method

Weight PM Cycle

Drum Type/Yield **Black Toner Yield** Black Developer Yield

**Power Supply** Power Consumption

**COPY FUNCTIONS** Special Features

KD1011 - Paper Feed Pedestal

MY1021 - Cassette Module

Indirect Electrostatic Photographic Method (Dry Process)

Laser Electronic CCD Line Sensor

Desktop with Fixed Frame Design

Stationary Platen

2400 x 600 dpi/256 Gradations 23/28 PPM (Letter) Approximately 25 Seconds Approximately 5.4 Seconds (Letter)

74,000/90,000 Copies Up to 999 Copies

Statement-R (5.5" x 8.5") to Ledger (11" x 17"), 17-28 lbs.; Stack Feed Bypass 17-53 lbs. (110 lbs. Index)

Standard Bond, Overhead Transparencies, Tab Sheets,

128 MB, 40 GB HDD 25% to 400%

Stack Feed Bypass (100 Sheets), Envelopes Graphic Display; Icon Based LCD Touch Panel; Key Top 2 Standard Cassettes @ 550 Sheets (17-28 lbs.); 100-Sheet Stack Feed Bypass

AutomaticToner Density Monitoring and Dispensing from Toner Cartridge

25.1" x 28.15" x 29.09" (W x D x H)

Approximately 165 lbs 74.000/90.000

Organic Photoconductor/120,000

22 000 74,000/90,000 115 Volts; 60 Hz Maximum 1.5 kW

Access Codes (1.000), Alternation, Annotation, AMS/APS

Access Codes (1,000), Alternation, Annotation, AMS/APS (RADF & Original Glass Except Bypass), Auto Job Start, Auto Cassette Change, Auto Trayless Duplex, Auto Energy Saver, Auto Sleep Mode, Cover Sheet, Dual Page Copying, Edge Erase, e-Filing, Electronic Sort, Energy Saver, Image Shift, Interrupt Memory, Job Build, Job Memory - Templates, Job Reservation (Scan Ahead) - 5 Jobs, Magazine Sort (Booklet Making Mode), Mirror Image, Negative/Positive, Page Numbering, Sheet Insertion,Text,Text/Photo, & Photo Modes, Weekly Timer, X-Y Zoom, 2-in-1, 4-in-1, 8-in-1 Copy Mode

# COPY OPTIONS

MR3016 – Reversing Automatic Document Feeder (RADF)

KD1012 - Large Capacity Tray

MJ5004 - Job Separator

MJ5005 - Offset Catch Tray MJ1022 – Single-Position Hanging Finisher

MJ1025 - Multi-Position Stapling Finisher With Saddle-Stitch

KN3520 - Bridge Kit MJ6005 - Hole Punch Unit KA3511 - Platen Cover

KK3511 - Work Tray

Stack Up to 100 Letter/Letter-R Sized Originals; 100 Legal or Ledger Sized Originals Simplex (13-33 lbs.), Duplex (13-28 lbs.); Automatically Refeeds Two-Sided Originals For One-Sided Copying or Two-Sided Copying; Copying Speed Using RADF: 45

550-Sheet Pedestal; Statement-R to Ledger (17-28 lbs.); Able to be Upgraded with Second 550-Sheet Statement-R to Ledger Tray (17-28 lbs.)

550-Sheet Drawer; Statement-R to Ledger (17-28 lbs.)

2,500-Sheet Drawer; Letter (17-28 lbs.); Stacks Side-By-Side (2  $\times$  1,250)

Attaches to Inner Exit Compartment; Upper Tray 150-Sheet Capacity, Lower Tray 250-Sheet Capacity Attaches to Inner Exit Compartment; 250-Sheet Paper Capacity

2Tray; Hanging Design; Non-Sort/Sort/Group/Staple Sort; Output: Face Down; Paper Size: Statement.R to Ledger.Tray 1 Stack Capacity: 200 Sheets (Lt); Tray 2 Stack Capacity: 700 Sheets (Lt); Staple Capacity: 30 Sheets (Lt/Lt-R, 22 lbs.); Locations: Rear Single Position Staple (Slant)

1 Tray + Saddle-Stitch Tray; Console Design; Non-Sort/Sort/ Group/Staple Sort; Output: Face Down; Paper Size: Statement-R to Ledger. Tray 1 Stack Capacity: 1,000 Sheets (Ltl; Staple Capacity: 50 Sheets (Ltl-R, 22 lbs.); Locations: Front Corner (Ltl-LR/Lg/Ld); Rear Corner - Slant/Parallel (Lt-R/Lg); Center (2) (Lt/Ld); Saddle-Stitch, 10-Sheet Capacity (Lt/Ld); Center Folding

Required with either the MJ1022 or MJ1025 Finishing Options

2 or 3 Hole Punch Capability (for MJ1025 Only)

Protective Cover for Glass Platen

Work Tray

#### PRINT FEATURES

266 MHz Processor Memory 128 MR: 40 GR HDD 2400 x 600 dpi (w/Smoothing) Print Resolution Print Speed Equivalent to Engine Speed **Duty Cycle** Equivalent to Engine Duty Cycle Standard: PCL6<sup>™</sup>, PostScript<sup>™</sup> 3 Page Description Language Support

1-999 **Multiple Prints** 

Page Orientation Portrait or Landscape Simplex/Duplex Simplex & Duplex Printing Available **Duplex Modes** Short Edge Bind/Long Edge Bind

Sort/Group/Alternation (With 2nd Paper Source; Finishing All Optional Finishing Capabilities

All Available Sources + Stack Feed Bypass

NetWare® 4.x, 5.x, 6.x, Windows® 98, 2000, Me, Windows® NT 4.0, XP, Citrix® Metaframe®, Macintosh® Network Operating Systems Support

**Protocol Support** IPX/SPX,TCP/IP, NetBEUI, EtherTalk®, LPR/LPD, IPP, WINS, SNMP, SMB Drivers

Windows® 98, 2000, Me, Windows® NT 4.0, XP; Macintosh® OS 8.6, 9.x, 10.x (With PPD), UNIX®

I/O Interfaces 10/100BaseT

Cover Page, DocMon® - Document Monitoring Utility, Magazine Sort, Mixed Size Printing, Overlays, Private Print, Proof Printing, Saddle-Stitch/Booklet Mode, Scheduled Print Sheet Insertion, Store-to-e-filing, Tab Print, TopAccess™ Device Management, Watermark Print Special Features

# SCAN FEATURES

Paper Sources

CCD Line Sensor Scanning Method **Gray Scale** 256 Gradations

Maximum Paper Size Input: Ledger, Output: Ledger **Maximum Scan Capacity** 1,000 Pages or Capacity of HDD Scan Resolution 150 dpi, 200 dpi, 300 dpi, 400 dpi, 600 dpi Scan Speed Up to 60 PPM, 45 PPM (@ 600 dpi) **Document Input** RADF or Platen

TIFF-MMR TIFF-S PDF File Format Special Features

Scan-to-File (HDD or Network Folder), Scan-to-FTP, Scan-to-Email, Scan-to-e-Filing, Scan-to-Twain, Scan-to-Internet Fax

#### **FACSIMILE FEATURES**

Operation Method Touch Screen Fax Panel or LAN-Fax

Compatibility Super G3 MH/MR/MMR/JBIG **Data Compression** Approx. 3 Seconds Per Page Transmission Speed

33.6 Kbps Fax Modem Speed

Fax Memory 240 MBTransmission: 120 MB Reception: 40 GB HDD Back-Up Memory Transmission 100 Jobs; 1,000 Destinations Max; 400 Destinations/Job

Scanning Method CCD Line Sensor

.7 Seconds Per Page: 50 Scans Per Minute Scan Speed

**Grav Scale** 256 Gradations Maximum Paper Size Input: Ledger, Output: Ledger

**Document Input** RADF or Platen Special Features

Automatic Redial (Up to 14Times), Broadcasting (Max. 1,000 Destinations), Chain Dialing, Delayed Transmission, Direct Transmission, Double Sided Scanning and Reception, Dual Access, Group Dialing (Max. 200 Groups/400 Destinations/Group), Optional Second Line, PC/LAN Faxing, Phone Book (1,000 Addresses), Polling, PriorityTransmission, Public Mailbox (F-Code), TX/RX Reporting

## **E-FILING FEATURES**

Operation Method Touch Screen Control Panel or Client PC Number of Boxes 1 Public Box: 200 Private User Boxes

Capacity of Boxes 100 Folders Per Box: 400 Documents Per Folder: 200 Pages Per Document

TIFF-MMR, TIFF-S, PDF, TAC File Format

Scan-to-e-Filing Box, Print-to-e-Filing Box, Fax-to-e-Filing Box, File Downloader Software, TWAIN Driver Utility Special Features

# **CONNECTIVITY OPTIONS**

GM1020 - Print Enabler **Enables Network Printing** 

GM2020 - Print & Scan Enabler Enables Network Printing & Network Scanning GM3020 - Scan Upgrade Enabler Enables Scanning; Requires Print Enabler (GM1020)

GD1150 - Fax Board Fax Board, 33.6 Kbps Modern GD1160 - 2nd PSTN Line Optional Second Line

GN1010 - Wireless LAN Adapter Enables Wireless 802.11b Network Printing GO1040 - PCI Slot Peripheral Component Interconnect Slot

Corporate Office: 2 Musick, Irvine, California 92618-1631

East Coast: 959 Route 46 East, 5th Floor, Parsippany, New Jersey 07054 Tel: 973/316-2700 Fax: 973/263-2393

Midwest: 8770 W. Bryn Mawr Avenue, Suite 700, Chicago, Illinois 60631 Tel: 773/380-6000 Fax: 773/380-8077

South: 4855 Peachtree Industrial Blvd., Suite 210, Norcross, Georgia 30092-3024 Tel: 770/209-8540 Fax: 770/209-8556

West Coast: 142 Technology, Suite 150, Irvine, California 92618 Tel: 949/462-6262 Fax: 949/462-2700

Web Site: www.copiers.toshiba.com or www.fax.toshiba.com

© 2004 Toshiba America Business Solutions, Inc., Electronic Imaging Division e-studio230/280 Spec Sheet/Inv. Code ES2302802

Designs and specifications subject to change without notice. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates, based on 6% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system.

AUTHORIZED TOSHIBA DEALER

